



Stiftkabelschuhe lötfrei ohne Isolation nach DIN 46230

Ausführung in SE-Cu
galvanisch verzinkt
Temperaturbeständig bis +125°C

* = nicht genormt nach DIN

Artikelnummer	Leiterquer- schnitt in mm ²	Abmessungen in mm			
		d1	d2	L1	L2
RSQ 5338 - 0,5	0,10-0,50	1,0	1,2	14,0	8,0
RSQ 5338 - 1	0,25-1,50	1,6	1,9	17,0	10,0
RSQ 5338 . 001-1	0,25-1,50	1,6	1,9	15,5	7,0
RSQ 5338 . 002-1	0,25-1,50	1,6	1,9	13,5	5,0
RSQ 5338 - 2,5	>1,0-2,5	2,3	1,9	17,0	10,0
RSQ 5338 . 001-2,5	>1,0-2,5	2,3	1,9	13,5	5,0
RSQ 5338 . 002-2,5	>1,0-2,5	2,3	1,9	22,5	14,0
RSQ 5338 - 6	>2,5-6,0	3,6	2,7	20,0	10,0
RSQ 5338 - 10	>6,0-10,0	4,5	4,3x2,4	22,0	12,0
RSQ 5338 - 16	>10,0-16,0	5,8	5,5x2,6	26,0	13,0
RSQ 5338 - 25	>16,0-25,0		6,8x2,6	33,5	20,0
RSQ 5338 - 35	>25,0-35,0		8,0x3,2	40,5	23,5
RSQ 5338 - 50	>35,0-50,0		9,5x3,8	45,0	26,0
RSQ 5338 - 70	>50,0-70,0		11,0x4,1	55,0	31,0
RSQ 5338 - 95	>70,0-95,0		12,5x5,2	55,0	31,0



**Albert
Schäfer
Nachf.**

Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de