



## Kabelschuhe lötfrei Gabelform ohne Isolation

Ausführung in SE-CU

galvanisch verzinkt

Temperaturbeständig bis +125°C

\* = nicht genormt nach DIN

Artikelnummer			Leiterquer- schnitt in mm <sup>2</sup>	Bolzen Nenngröße		Abmessungen in mm			
				M	Din	d1	d3	L	
RSQ 7180	C	3-0,5	0,10-0,50	3,0	*	1,0	5,0	10	
RSQ 7103	C	3-1	0,25-1,50	3,0	*	1,6	6,0	10,8	
RSQ 7103	C	3,5-1	0,25-1,50	3,5	*	1,6	6,0	11,0	
RSQ 7154	C	4-1	0,25-1,50	4,0	*	1,6	7,0	12,0	
RSQ 7104	C	4-1	0,25-1,50	4,0	*	1,6	8,0	11,8	
RSQ 7105	C	5-1	0,25-1,50	5,0	*	1,6	10,0	12,8	
RSQ 7158	C	6-1	0,25-1,50	6,0	*	1,6	11,0	14,8	
RSQ 7159	C	3-2,5	>1,0-2,5	3,0	*	2,3	6,0	11,0	
RSQ 7160	C	3,5-2,5	>1,0-2,5	3,5	*	2,3	6,8	11,0	
RSQ 7160	C	4-2,5	>1,0-2,5	4,0	*	2,3	6,8	11,0	
RSQ 7108	C	4-2,5	>1,0-2,5	4,0	*	2,3	8,0	11,8	
RSQ 7109	C	5-2,5	>1,0-2,5	5,0	*	2,3	10,0	13,8	
RSQ 7110	C	6-2,5	>1,0-2,5	6,0	*	2,3	11,0	15,8	
RSQ 7155	C	4-6	>2,5-6,0	4,0	*	3,6	8,0	14,0	
RSQ 7112	C	5-6	>2,5-6,0	5,0	*	3,6	10,0	15,0	
RSQ 7114	C	6-6	>2,5-6,0	6,0	*	3,6	11,0	16,0	
RSQ 7115	C	8-6	>2,5-6,0	8,0	*	3,6	14,0	19,0	
RSQ 7119	C	4-10	>6,0-10,0	4,0	*	4,5	10,0	16,0	
RSQ 7119	C	5-10	>6,0-10,0	5,0	*	4,5	10,0	16,0	
RSQ 7120	C	6-10	>6,0-10,0	6,0	*	4,5	11,0	17,0	
RSQ 7125	C	6-16	>10,0-16,0	6,0	*	5,8	11,0	20,0	
RSQ 7125	C	8-16	>10,0-16,0	8,0	*	5,8	14,0	22,0	



**Albert  
Schäfer  
Nachf.**

Albert Schäfer Nachf. GmbH  
Forststraße 154  
70193 Stuttgart

Telefon: 0711 633037-0  
Telefax: 0711 633037-29  
eMail: verkauf@albert-schaefer.de