



Kabelschuhe lötfrei Ringform ohne Isolation nach DIN 46234

Ausführung in Cu-OF

galvanisch verzinkt

Temperaturbeständig bis +125°C

Artikelnummer Leiterquer- Bolzen Abmessungen in mm
* = nicht genormt nach DIN schnitt in mm² M

d1 d2 d3 L a

| | | | | | | | |
|---------------|-----------|-----|-----|-----|-----|----|---|
| SQ 80A2-0,5 | 0,10-0,50 | 2,0 | 1,0 | 2,2 | 5,0 | 10 | 4 |
| SQ 80A3-0,5 | 0,10-0,50 | 3,0 | 1,0 | 3,2 | 5,0 | 10 | 4 |
| SQ 80A3,5-0,5 | 0,10-0,50 | 3,5 | 1,0 | 3,2 | 6,0 | 12 | 4 |
| SQ 81A4-0,5 | 0,10-0,50 | 4,0 | 1,0 | 4,3 | 6,5 | 12 | 4 |
| SQ 82A5-0,5 | 0,10-0,50 | 5,0 | 1,0 | 5,3 | 8,0 | 11 | 4 |

| | | | | | | | |
|-------------|----------|------|-----|------|------|----|---|
| SQ 03A2-1 | 0,50-1,0 | 2,0 | 1,6 | 2,2 | 6,0 | 11 | 5 |
| SQ 03A2.5-1 | 0,50-1,0 | 2,5 | 1,6 | 2,7 | 6,0 | 11 | 5 |
| SQ 03A3-1 | 0,50-1,0 | 3,0 | 1,6 | 3,2 | 6,0 | 11 | 5 |
| SQ 03A3.5-1 | 0,50-1,0 | 3,5 | 1,6 | 3,7 | 6,0 | 11 | 5 |
| SQ 54A4-1 | 0,50-1,0 | 4,0 | 1,6 | 4,3 | 7,0 | 11 | 5 |
| SQ 04A4-1 | 0,50-1,0 | 4,0 | 1,6 | 4,3 | 8,0 | 12 | 5 |
| SQ 04A5-1 | 0,50-1,0 | 5,0 | 1,6 | 5,3 | 8,0 | 12 | 5 |
| SQ 05A5-1 | 0,50-1,0 | 5,0 | 1,6 | 5,3 | 10,0 | 13 | 5 |
| SQ 58A6-1 | 0,50-1,0 | 6,0 | 1,6 | 6,5 | 10,0 | 17 | 5 |
| SQ 58A8-1 | 0,50-1,0 | 8,0 | 1,6 | 8,4 | 12,0 | 17 | 5 |
| SQ 58A10-1 | 0,50-1,0 | 10,0 | 1,6 | 10,5 | 14,0 | 17 | 5 |

| | | | | | | | |
|----------------|---------|------|-----|------|------|------|---|
| SQ 59A3-2,5 | 1,5-2,5 | 3,0 | 2,3 | 3,2 | 6,0 | 11,0 | 5 |
| SQ 59A3,5-,2,5 | 1,5-2,5 | 3,5 | 2,3 | 3,7 | 6,0 | 11,0 | 5 |
| SQ 60A3,5-,2,5 | 1,5-2,5 | 4,0 | 2,3 | 3,7 | 6,8 | 11,0 | 5 |
| SQ 08A4-2,5 | 1,5-2,5 | 4,0 | 2,3 | 4,3 | 8,0 | 12,0 | 5 |
| SQ 08A5-2,5 | 1,5-2,5 | 5,0 | 2,3 | 5,3 | 8,0 | 12,0 | 5 |
| SQ 09A5-2,5 | 1,5-2,5 | 5,0 | 2,3 | 5,3 | 10,0 | 14,0 | 5 |
| SQ 09A6-2,5 | 1,5-2,5 | 6,0 | 2,3 | 6,5 | 10,0 | 14,0 | 5 |
| SQ 10A6-2,5 | 1,5-2,5 | 6,0 | 2,3 | 6,5 | 11,0 | 16,0 | 5 |
| SQ 62A8-2,5 | 1,5-2,5 | 8,0 | 2,3 | 8,4 | 14,0 | 17,0 | 5 |
| SQ 51A10-2,5 | 1,5-2,5 | 10,0 | 2,3 | 10,5 | 18,0 | 20,0 | 5 |
| SQ 51A12-2,5 | 1,5-2,5 | 12,0 | 2,3 | 13 | 18,0 | 20,0 | 5 |

| | | | | | | | |
|------------|---------|------|-----|------|------|------|---|
| SQ 55A4-6 | 4,0-6,0 | 4,0 | 3,6 | 4,3 | 8,0 | 14,0 | 6 |
| SQ 12A5-6 | 4,0-6,0 | 5,0 | 3,6 | 5,3 | 10,0 | 15,0 | 6 |
| SQ 14A6-6 | 4,0-6,0 | 6,0 | 3,6 | 6,5 | 11,0 | 16,0 | 6 |
| SQ 15A8-6 | 4,0-6,0 | 8,0 | 3,6 | 8,4 | 14,0 | 19,0 | 6 |
| SQ 17A10-6 | 4,0-6,0 | 10,0 | 3,6 | 10,5 | 18,0 | 21,0 | 6 |
| SQ 17A12-6 | 4,0-6,0 | 12,0 | 3,6 | 13 | 18,0 | 21,0 | 6 |



Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de



| Artikelnummer * = nicht genormt nach DIN | Leiterquer- schnitt in mm ² | Bolzen M | Abmessungen in mm | | | | |
|---|---|-------------|-------------------|------|------|------|----|
| | | | d1 | d2 | d3 | L | a |
| SQ 19A4-10 | 10,0 | 4,0 | 4,5 | 4,3 | 10,0 | 16,0 | 8 |
| SQ 19A5-10 | 10,0 | 5,0 | 4,5 | 5,3 | 10,0 | 16,0 | 8 |
| SQ 20A6-10 | 10,0 | 6,0 | 4,5 | 6,5 | 11,0 | 17,0 | 8 |
| SQ 21A8-10 | 10,0 | 8,0 | 4,5 | 8,4 | 14,0 | 20,0 | 8 |
| SQ 22A10-10 | 10,0 | 10,0 | 4,5 | 10,5 | 18,0 | 21,0 | 8 |
| SQ 23A12-10 | 10,0 | 12,0 | 4,5 | 13 | 22,0 | 23,0 | 8 |
| SQ 25A5-16 | 16,0 | 5,0 | 5,8 | 5,3 | 11,0 | 20,0 | 10 |
| SQ 25A6-16 | 16,0 | 6,0 | 5,8 | 6,5 | 11,0 | 20,0 | 10 |
| SQ 26A8-16 | 16,0 | 8,0 | 5,8 | 8,4 | 14,0 | 22,0 | 10 |
| SQ 27A10-16 | 16,0 | 10,0 | 5,8 | 10,5 | 18,0 | 24,0 | 10 |
| SQ 28A12-16 | 16,0 | 12,0 | 5,8 | 13 | 22,0 | 26,0 | 10 |
| SQ 56A5-25 | 25,0 | 5,0 | 7,5 | 5,3 | 12,0 | 25,0 | 11 |
| SQ 56A6-25 | 25,0 | 6,0 | 7,5 | 6,5 | 12,0 | 25,0 | 11 |
| SQ 30A6-25 | 25,0 | 6,0 | 7,5 | 6,5 | 16,0 | 25,0 | 11 |
| SQ 30A8-25 | 25,0 | 8,0 | 7,5 | 8,4 | 16,0 | 25,0 | 11 |
| SQ 31A10-25 | 25,0 | 10,0 | 7,5 | 10,5 | 18,0 | 26,0 | 11 |
| SQ 32A12-25 | 25,0 | 12,0 | 7,5 | 13 | 22,0 | 31,0 | 11 |
| SQ 11A16-25 | 25,0 | 16,0 | 7,5 | 17 | 28,0 | 35,0 | 11 |
| SQ 29A6-35 | 35,0 | 6,0 | 9,0 | 6,5 | 15,0 | 26,0 | 12 |
| SQ 34A8-35 | 35,0 | 8,0 | 9,0 | 8,4 | 16,0 | 26,0 | 12 |
| SQ 75A10-35 | 35,0 | 10,0 | 9,0 | 10,5 | 18,0 | 27,0 | 12 |
| SQ 35A12-35 | 35,0 | 12,0 | 9,0 | 13 | 22,0 | 31,0 | 12 |
| SQ 12A16-35 | 35,0 | 16,0 | 9,0 | 17 | 28,0 | 36,0 | 12 |
| SQ 87A20-35 | 35,0 | 20,0 | 9,0 | 21 | 30,0 | 37,5 | 14 |
| SQ 36A6-50 | 50,0 | 6,0 | 11,0 | 6,5 | 18,0 | 34,0 | 16 |
| SQ 36A8-50 | 50,0 | 8,0 | 11,0 | 8,4 | 18,0 | 34,0 | 16 |
| SQ 36A10-50 | 50,0 | 10,0 | 11,0 | 10,5 | 18,0 | 34,0 | 16 |
| SQ 37A12-50 | 50,0 | 12,0 | 11,0 | 13 | 22,0 | 36,0 | 16 |
| SQ 39A16-50 | 50,0 | 16,0 | 11,0 | 17 | 28,0 | 40,0 | 16 |
| SQ 93A20-50 | 50,0 | 20,0 | 11,0 | 21 | 32,0 | 41,5 | 18 |
| SQ 40A6-70 | 70,0 | 6,0 | 13,0 | 6,5 | 22,0 | 38,0 | 18 |
| SQ 40A8-70 | 70,0 | 8,0 | 13,0 | 8,4 | 22,0 | 38,0 | 18 |
| SQ 40A10-70 | 70,0 | 10,0 | 13,0 | 10,5 | 22,0 | 38,0 | 18 |
| SQ 40A12-70 | 70,0 | 12,0 | 13,0 | 13 | 22,0 | 38,0 | 18 |
| SQ 42A16-70 | 70,0 | 16,0 | 13,0 | 17 | 28,0 | 42,0 | 18 |
| SQ 88A20-70 | 70,0 | 20,0 | 13,0 | 21 | 32,0 | 45,0 | 19 |
| SQ 44A8-95 | 95,0 | 8,0 | 15,0 | 8,4 | 24,0 | 42,0 | 20 |
| SQ 44A10-95 | 95,0 | 10,0 | 15,0 | 10,5 | 24,0 | 42,0 | 20 |
| SQ 44A12-95 | 95,0 | 12,0 | 15,0 | 13 | 24,0 | 42,0 | 20 |
| SQ 45A16-95 | 95,0 | 16,0 | 15,0 | 17 | 28,0 | 44,0 | 20 |
| SQ 45A20-95 | 95,0 | 20,0 | 15,0 | 17 | 32,0 | 51,8 | 20 |



Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de



| Artikelnummer *= nicht genormt nach DIN | Leiterquer- schnitt in mm ² | Bolzen M | Abmessungen in mm | | | | |
|--|---|-------------|-------------------|------|------|------|----|
| | | | d1 | d2 | d3 | L | a |
| SQ 46A8-120 | 120,0 | 8,0 | 16,5 | 8,4 | 24,0 | 44,0 | 22 |
| SQ 46A10-120 | 120,0 | 10,0 | 16,5 | 10,5 | 24,0 | 44,0 | 22 |
| SQ 46A12-120 | 120,0 | 12,0 | 16,5 | 13 | 24,0 | 44,0 | 22 |
| SQ 47A16-120 | 120,0 | 16,0 | 16,5 | 17 | 28,0 | 48,0 | 22 |
| SQ 25A20-120 | 120,0 | 20,0 | 16,5 | 21 | 32,0 | 53,0 | 21 |
| SQ 49A10-150 | 150,0 | 10,0 | 19,0 | 10,5 | 30,0 | 50,0 | 24 |
| SQ 49A12-150 | 150,0 | 12,0 | 19,0 | 13 | 30,0 | 50,0 | 24 |
| SQ 49A16-150 | 150,0 | 16,0 | 19,0 | 17 | 30,0 | 50,0 | 24 |
| SQ 15A18-150 | 150,0 | 18,0 | 19,0 | 17 | 36,0 | 63,0 | 24 |
| SQ 15A20-150 | 150,0 | 20,0 | 19,0 | 21 | 36,0 | 63,0 | 27 |
| SQ 72A10-185 | 185,0 | 10,0 | 21,0 | 10,5 | 36,0 | 50,0 | 28 |
| SQ 72A12-185 | 185,0 | 12,0 | 21,0 | 13 | 36,0 | 50,0 | 28 |
| SQ 72A16-185 | 185,0 | 16,0 | 21,0 | 17 | 36,0 | 50,0 | 28 |
| SQ 23A18-185 | 185,0 | 18,0 | 21,0 | 17 | 38,5 | 67,5 | 28 |
| SQ 72A20-185 | 185,0 | 20,0 | 21,0 | 21 | 36,0 | 50,0 | 28 |
| SQ 73A10-240 | 240,0 | 10,0 | 23,5 | 10,5 | 38,0 | 56,0 | 32 |
| SQ 73A12-240 | 240,0 | 12,0 | 23,5 | 13 | 38,0 | 56,0 | 32 |
| SQ 73A16-240 | 240,0 | 16,0 | 23,5 | 17 | 38,0 | 56,0 | 32 |
| RSQ 7217A18-240 | 240,0 | 18,0 | 23,5 | | 44,0 | 69,0 | |
| RSQ 7217A20-240 | 240,0 | 20,0 | 23,5 | | 44,0 | 69,0 | |
| RSQ 7217A22-240 | 240,0 | 22,0 | 23,5 | | 44,0 | 69,0 | |
| RSQ 7217A32-240 | 240,0 | 32,0 | 23,5 | | 44,0 | 69,0 | |



**Albert
Schäfer
Nachf.**

Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de