



Kabelschuhe lötfrei Ringform isoliert mit PVC nach DIN 46237

RSP = PVC -75°C

Artikelnummer	Leiterquer- schnitt in mm ²	Kenn- farbe	Abmessung in mm				
			d	B	L	D	E
SPD 03A2,5-1	0,50-1,50	rot	2,7	6,0	16,0	4,5	10,5
SPD 03A3-1	0,50-1,50	rot	3,2	6,0	16,0	4,5	10,5
SPD 04A3,5-1	0,50-1,50	rot	3,7	6,0	16,0	4,5	10,5
SPD 04A4-1	0,50-1,50	rot	4,3	8,0	17,0	4,5	10,5
SPD 05A5-1	0,50-1,50	rot	5,3	10,0	18,0	4,5	10,5
SPD 05A6-1	0,50-1,50	rot	6,5	11,0	20,0	4,5	10,5
SPD 58A8-1	0,50-1,50	rot	8,4	14,0	29,5	4,5	10,5
SPD 58A10-1	0,50-1,50	rot	10,5	18,0	33,5	4,5	10,5
SPD 59A3-2,5	1,50- 2,50	blau	3,2	6,0	17,0	5,0	11,0
SPD 60A3,5-2,5	1,50- 2,50	blau	3,7	6,0	17,0	5,0	11,0
SPD 59A4-2,5	1,50- 2,50	blau	4,3	8,0	18,0	5,0	11,0
SPD 60A5-2,5	1,50- 2,50	blau	5,3	10,0	20,0	5,0	11,0
SPD 08A6-2,5	1,50- 2,50	blau	6,5	11,0	22,0	5,0	11,0
SPD 08A8-2,5	1,50- 2,50	blau	8,4	14,0	30,0	5,0	11,0
SPD 60A10-2,5	1,50- 2,50	blau	10,5	18,0	34,0	5,0	11,0
SPD 55A4-6	4,00- 6,00	gelb	4,3	8,0	20,0	6,0	14,0
SPD 55A5-6	4,00- 6,00	gelb	5,3	10,0	21,0	6,0	14,0
SPD 55A6,5-6	4,00- 6,00	gelb	6,5	11,0	22,0	6,0	14,0
SPD 56A8-6	4,00- 6,00	gelb	8,4	14,0	25,0	6,0	14,0
SPD 12A10-6	4,00- 6,00	gelb	10,5	18,0	27,0	6,0	14,0
SPD 12A13-6	4,00- 6,00	gelb	13,0	19,0	32,0	6,0	14,0

